

(12) United States Patent Allen, IV et al.

(54) ELECTROSURGICAL INSTRUMENT

(75) Inventors: James D. Allen, IV, Broomfield, CO (US); Ryan C. Artale, Boulder, CO (US); Kim V. Brandt, Loveland, CO (US); Dennis W. Butcher, Longmont, CO (US); Edward M. Chojin, Boulder, CO (US); Keir Hart, Lafayette, CO (US); Russell D. Hempstead, Lafayette, CO (US); Glenn A. Horner, Boulder, CO (US); Daniel A. Joseph, Golden, CO (US); Duane E. Kerr, Loveland, CO (US); Dylan R. Kingsley, Broomfield, CO (US); Peter M. Mueller, Frederick, CO (US); Jessica E. C. Olson, Frederick, CO (US); John R. Twomey, Longmont, CO (US); Jeffrey R. Unger, Longmont, CO

(73) Assignee: **COVIDIEN LP**, Mansfield, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1049 days.

Appl. No.: 13/236,168

Sep. 19, 2011 (22)Filed:

(65)**Prior Publication Data**

US 2013/0072927 A1 Mar. 21, 2013

(51) Int. Cl. A61B 18/14 (2006.01)A61B 17/29 (2006.01)(Continued)

(52) U.S. Cl. CPC A61B 18/1447 (2013.01); A61B 17/29 (2013.01); A61B 17/32 (2013.01); (Continued)

US 9,636,169 B2 (10) Patent No.: (45) **Date of Patent:**

May 2, 2017

(58) Field of Classification Search

CPC A61B 2017/2926; A61B 10/06; A61B 17/1608; A61B 17/29; A61B 17/320016; (Continued)

(56)References Cited

U.S. PATENT DOCUMENTS

9/1978 Pike D249,549 S 4,151,846 A 5/1979 von Zeppelin et al. (Continued)

FOREIGN PATENT DOCUMENTS

CN201299462 9/2009 DE 2415263 10/1975 (Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 08/926,869, filed Sep. 10, 1997, James G. Chandler. (Continued)

Primary Examiner — Christopher D Koharski Assistant Examiner — Pamela M Bays

(57)ABSTRACT

An electrosurgical forceps is provided with a shaft that extends from a housing of the electrosurgical forceps. An end effector assembly includes a pair of first and second jaw members pivotably coupled to one another via a pivot pin. One or both of the first and second jaw members may be movable from an open position for positioning tissue therebetween to a clamping position for grasping tissue. A detent is operably disposed proximal the pivot pin and extends radially outward from a proximal flange of one of the jaw members. The detent is configured to releasably engage a corresponding slot disposed on a proximal flange of the other jaw member. The detent and slot are configured to control a gap distance between the first and second jaw members when the first and second jaw members are in the clamping position.

2 Claims, 2 Drawing Sheets

